

Delivering science and technology
to protect our nation
and promote world stability

Chlorine Worth Study in Support of PF-4 Operations

Theresa Cutler, Travis Grove, Jesson
Hutchinson, Kelsey Amundson, Nick Wynne,
Travis Smith

February 2022

LA-UR-22-21223

Motivation

- Aqueous Chloride Operations at PF-4 are important:
 - Recover Pu from pyrochemical residues
 - Reduces waste sent to WIPP
 - Increased throughput for Am production
- Aqueous Chloride Operations have very conservative mass limits (~520 grams Pu)
 - Significant amounts of Chlorine but calculations not crediting Cl-35 neutron absorption
 - Accounting for Cl-35 absorption leads to higher mass limits
- Can experiments be designed/conducted to provide technical justification to NCS in order to increase mass limits?



**This is in direct support of 30 pits per year mission,
one of the top priorities for NNSA**



Timeline (ACCELERATED)

- Initial tasking: June 2020
- Preliminary Design Complete (CED-1 equivalent): November 2020
- Final Design Complete (CED-2 equivalent): March 2021
- Part Receipt and Inspection Complete (CED-3a equivalent): October 2021
- Experiment Execution (CED-3b equivalent): December 2021
- Experiment Documentation Write-up Complete (start CED-4a equivalent):
January 2022
- ICSBEP Target (CED-4a equivalent): Fall 2022





Design Process

- Experiment Design Process related to the 2019 ARCHIMEDES LDRD project
 - See the current LDRD EUCLID project for in-depth information
- Design Process:
 - Examine application Pu concentration ranges and associated CI-35 (n, γ) sensitivities
 - Determine specific Pu concentration applications that cover concentration ranges
 - Develop multiple generic experimental benchmarks
 - Materials, geometries
 - Compare experimental benchmark designs to these applications (CI-35 (n, γ) sensitivities, i.e. c_k and partial c_k)
 - Iterate on benchmark design
- Note: c_k and partial c_k are similarity coefficients that utilize model sensitivities to nuclear data and uncertainties associated with that nuclear data
 - What is the best way to determine if two models are “similar”?




Gap Analysis (Comparison to Existing Benchmarks)






- A comparison to existing experiments was performed.
- Very few benchmarks sensitive to Cl-35 (n,γ) exist.
- The sensitivity of these benchmarks is much lower than the application.

Final Designs

- Reflector: 3" HDPE (top, bottom, sides)
- Fuel: 5x4 (20 total per unit) ZPPR plates, ~105 g Pu per plate
- Moderator: HDPE (varying geometry)
- CI Material: PVC or CPVC (varying geometry)
- Configurations:
 1. optimized for 30 g/L application (covers 20-100 g/L range)
 - Stack of HDPE-PVC-HDPE on ZPPR plates
 2. optimized for 300 g/L application (covers 300-400 g/L range)
 - ~7.9" diameter PVC cylinder inside HDPE on ZPPR plates
 3. optimized for 600 g/L application (covers 500-600 g/L range)
 - ~7.9" diameter CPVC cylinder inside HDPE on ZPPR plates



Final Designs



Unit: Configuration 1
Not to Scale
Dimensions are nominal

- 0.06" PVC Moderator (height)
- 0.39" HDPE Moderator (height)
- 0.11" ZPPR Plate Layer (height)
- 0.13" Al Tray (height) and 0.25" Frame (thick)

Unit: Configuration 2
Not to Scale
Dimensions are nominal

- 7.9" PVC Moderator (diameter)
- 0.71" HDPE Moderator (height)
- 0.11" ZPPR Plate Layer (height)
- 0.13" Al Tray (height) and 0.25" Frame (thick)


Unit: Configuration 3
Not to Scale
Dimensions are nominal

- 7.9" CPVC Moderator (diameter)
- 0.87" HDPE Moderator (height)
- 0.11" ZPPR Plate Layer (height)
- 0.13" Al Tray (height) and 0.25" Frame (thick)


- Note that Al Tray and Al frame (shown in grey) is used to conduct heat out of assembly
 - For the top partial stack, “bottom” ZPPR tray (and shroud) sits directly on membrane/top stationary platform
 - For the bottom partial stack, the shroud goes through the bottom reflector and directly touches the platen




Sensitivity Plots: Cl-35 (n, γ)



Configuration 1
20-100 g/L



Configuration 2
300-400 g/L




Configuration 3
500-600 g/L



Gap Considerations

- Compression rods screw into membrane (very small thread length)
 - Compression spacers provide additional surface and separation distance of steel nut from assembly
- Compression plate, studs, spacers and nuts reduce gaps which cause significant neutron streaming paths in assembly
 - Residual gaps measured with shim gauges during experiment



Lateral Gap Considerations

- For lateral gaps, the goal is to align the top and bottom stacks together with known uncertainties
 - Membrane has slight divot in top and bottom sides that the top and bottom stacks align into
 - Assured alignment by operating in LOCAL mode before starting remote approach
 - Imperfect alignment will cause reactivity loss, which is accentuated by the divot
 - Provides a visual indication of alignment from control room (through cameras)



Membrane with divot



Results






Measured Results

Configuration	Measured Reactor Period (seconds)	Associated Excess Reactivity (cents)	Maximum Observed ΔT ($^{\circ}\text{C}$)
1	57.6	16.5	7.4
2	58.1	16.4	14.4
3	85.8	12.4	16.1



Configuration 1: 30 g/L

- Final configuration: 8 units
 - 4 full units on bottom
 - 3 full units on top
 - Partial unit on top of top (Al is aluminum plates nearly matching Pu plate dimensions)
 - RTDs
 - Every unit on bottom
 - Top three units on top



Configuration 2: 300 g/L

- Final configuration: 14 units
 - 7 full units on bottom
 - 7 full units on top
 - 0.875" top reflector (reduced from 3.000")
 - RTDs
 - 5 of 7 units
 - 5 of 7 units





With and without side reflector



Configuration 3: 600 g/L

- Final configuration: 18 units
 - 10 full units on bottom
 - 7 full units on top
 - Partial unit on top of top (Al is aluminum plates nearly matching Pu plate dimensions)
 - RTDs
 - Top: 6 of 8 units
 - Bottom: 5 of 10 units



Physical Measurements

- Previous benchmark experiments have taught us a lot!
 - Many physical measurements required
 - Heights, gaps rotation, levelness
 - Samples of plastics received and sent out for detailed chemical analysis



Preliminary Results

- Simplified MCNP geometry
 - Includes detailed Pu plates
 - Does not include gaps
 - Does not include detailed compositions

Configuration	Experiment	Calculated	Partial c_k Cl-35 (n, γ)
1	1.00035	1.00613	0.94 (30g/L)
2	1.00034	1.01211	0.99 (300 g/L)
3	1.00026	1.00199	0.99 (600 g/L)



Future Work

- Draft ICSBEP benchmark
 - Target Fall 2022 Review Group Meeting, which means full completion by August 2022
 - Poly, PVC, CPVC chemical analysis
 - Received samples with parts
 - Requests out to companies for quotes; usual company no longer doing full analysis
 - Evaluate measurement uncertainty
 - Detailed (very detailed) MCNP model
 - Section 1 rough draft complete



PF-4 Operations Team Engagement

- Aqueous Chloride Operations Personnel Attended 2nd week
 - Supervisor, process engineers, operators
 - Participated in 1/M process
 - Loaded fuel
 - Felt PERSONALLY connected to the work



Acknowledgements



- This work was funded under the Material Recycle and Recovery Program, NNSA Plutonium Program Office (NA-191), under Office of Production Modernization (NA-19), funded and managed by the National Nuclear Security Administration for the Department of Energy
- NCERC is supported by the DOE Nuclear Criticality Safety Program, funded and managed by the National Nuclear Security Administration for the Department of Energy
- This work was supported by the US Department of Energy through the Los Alamos National Laboratory. Los Alamos National Laboratory is operated by Triad National Security, LLC, for the National Nuclear Security Administration of the US Department of Energy under Contract No. 89233218C

