



# IER-523: Design of a $\text{UO}_2\text{-BeO}$ Critical Experiment at Sandia

Mac Cook, Elijah Lutz, David Ames, Ashley Raster, James Cole, Gary Harms, John Miller

2023 DOE Nuclear Criticality Safety Program Technical Program Review

February 21-23, 2023

Hosted by Sandia National Laboratories



Sandia National Laboratories is a multimission laboratory managed and operated by National Technology and Engineering Solutions of Sandia LLC, a wholly owned subsidiary of Honeywell International Inc. for the U.S. Department of Energy's National Nuclear Security Administration under contract DE-NA0003525.

SAND2023-12611PE



# Background




## Annular Core Research Reactor (ACRR)


- Water-moderated pool-type research reactor
- Uranium dioxide-beryllium oxide ( $\text{UO}_2\text{-BeO}$ ) fuel
- Enrichment: 35 wt%
- 21.5 wt%  $\text{UO}_2$  – 78.5 wt% BeO
- Density ( $\text{UO}_2\text{-BeO}$ )  $\sim 3.4 \text{ g/cm}^3$
- Significant amounts of unused fuel
  - Elements ( $\sim 25$  elements and 2.8 kg  $^{235}\text{U}$  total)\*
  - Loose pellets ( $\sim 2 \text{ kg } ^{235}\text{U}$ )
- Data from historical records (fuel composition and geometry)

# Background

Fuel element




UO<sub>2</sub>BeO fuel pellets




## ACRR fuel element

- Stainless-steel cladding
  - OD~3.75 cm
  - L~54.5 cm
- Trifluted end fittings
- 5 niobium insulation cups
- 4 fuel pellet pieces formed into a disk and stacked in niobium cups

## UO<sub>2</sub>-BeO fuel pellets




# Background



## Sandia Critical Experiments (SCX)

- 7uPCX
- Enrichment: 6.9 wt%
- 2175 fuel rods
  - OD ~0.6 cm
  - Fueled length ~48.8 cm
- Approach-to-critical experiments
  - Number of fuel rods and water height
  - Six critical benchmark evaluations (ICSBEP)
- Flexibility in design
  - Authorization Basis allows modifications to accommodate designs outside the current limits




---

# Anticipated Critical Configurations

IER-523: CED-1

# Experiment Designs


- Both the loose BeO fuel pellets and the spare ACRR fuel elements were considered in CED-0
- In CED-1 phase, designs focused primarily on fuel element concepts
  - Pellet models (evolved from CED-0) are still presented and analyzed in CED-1 as prospective alternatives




# Experiment Design – Element Models

## Element Models

- Central test region containing 7 or 19 BeO fuel elements
- Driver region = 7uPCX fuel rods
  - Tight-packed (hex pitch = 0.86 cm)
  - Loose-packed (hex pitch = 1.72 cm)
- Fully reflected and water moderated
- Additional moderator/reflector configurations
  - Be metal rods
  - BeO rods








Top Cross Section View



Side Cross Section View







# Experiment Design – 19 BeO Element Configurations



-  Be Metal Rod
-  BeO Rod

Radial Cross Section View

# Experiment Design – 7 BeO Element Configurations



- Be Metal Rod
- BeO Rod

Radial Cross Section View

# Experiment Design – Element Models Summary

Config. #	# of 7uPCX	7uPCX Pitch (cm)	# of BeO Fuel	Ref. Rods	Mod. Rods	k-eff	Std. Dev.	EANLF (MeV)	3-Group Fission Fractions		
									<0.625 eV	0.625 eV - 100 keV	>100 keV
1	1129	0.86	19	None	None	1.0004	0.0007	3.64E-07	78%	17%	5%
2	264	1.72	19	None	None	0.9994	0.0006	9.03E-08	91%	8%	2%
3	1368	0.86	7	None	None	0.9992	0.0007	4.37E-07	77%	17%	6%
4	313	1.72	7	None	None	0.9996	0.0006	7.48E-08	93%	6%	2%
5	925	0.86	19	Be	None	1.0001	0.0007	3.52E-07	79%	17%	5%
6	284	1.72	19	Be	Be	1.0002	0.0007	1.13E-07	88%	10%	2%
7	1154	0.86	7	Be	None	0.9992	0.0007	4.31E-07	77%	17%	6%
8	347	1.72	7	Be	Be	0.9999	0.0006	9.46E-08	90%	8%	2%
9	900	0.86	19	BeO	None	0.9993	0.0007	3.51E-07	79%	17%	5%
10	288	1.72	19	BeO	BeO	0.9986	0.0007	1.14E-07	88%	10%	2%
11	1134	0.86	7	BeO	None	0.9998	0.0007	4.33E-07	77%	17%	6%
12	357	1.72	7	BeO	BeO	0.9993	0.0007	9.58E-08	90%	8%	2%

# Alternative Design – Loose Pellet Models

- Central test region containing pellets in stacked cassettes
  - Each cassette is 5x5 array of cells
  - Cells are filled by sets of pellet pieces
- Many designs considered
  - Four presented in following slides




≥ 1289 available





≥ 3795 available

# Experiment Design – UO<sub>2</sub>BeO Pellet Variations




Baseline Pellet Model – Most Similar to CED-0

	BeO Fuel (UO <sub>2</sub> -BeO)		3003 Aluminum
	7uP Fuel (UO <sub>2</sub> )		Air
	Water		Void
	Polyethylene (CH <sub>2</sub> )		Beryllium Oxide
	6061 Aluminum		AlBeMet






AlBeMet Tray Model



# Experiment Design - UO<sub>2</sub>BeO Pellet Variations



Offset Model



-  BeO Fuel (UO<sub>2</sub>-BeO)
-  7uP Fuel (UO<sub>2</sub>)
-  Water
-  Polyethylene (CH<sub>2</sub>)
-  6061 Aluminum
-  3003 Aluminum
-  Air
-  Void
-  Beryllium Oxide
-  AlBeMet




Poly-Al-X Model

# Experiment Design – Element Models Summary

Config.	# of 7uPCX	# of Half Disk	# of Crescent Moon	Averaged Enrichment	k-eff	EANLF (MeV)	3-Group Fission Fractions		
#							<0.625 eV	0.625 eV - 100 keV	>100 keV
BaselineP	1280	1750	1750	7.60%	1.002	3.02E-07	80%	15%	5%
AlBeMet	1280	1750	1750	7.60%	0.998	3.01E-07	80%	15%	5%
Offset	1280	2350	750	7.47%	1.001	2.97E-07	80%	15%	5%
Poly-Al-X	298	3000	1000	9.80%	1.006	7.49E-08	93%	6%	2%





---

# Calculations


IER-523: CED-1

# Sensitivity Analysis


- Sensitivities  $[(\Delta k/k)/(\Delta\sigma/\sigma)]$  computed for:
  - Various reactions
    - “Total Beryllium” Reaction is sum of  $^9\text{Be}$  elastic, inelastic, (n,2n), (n, $\gamma$ ), & (n, $\alpha$ ); be-o elastic, be-o inelastic, o-be elastic, and o-be inelastic; and be elastic and inelastic, as applicable
  - In energy 44-groups
  - For 12 Element Configurations,
  - 4 Pellet Configurations,
  - And selected existing Be benchmark models available at Sandia
    - HEU-COMP-INTER-003:  $\text{UH}_3$  powder reflected with beryllium
    - HEU-MET-INTER-009 and HEU-MET-THERM-027: BeO Bricks with HEU foils (“Spade” Experiments)

Configuration Identifier	3-Group Be Reaction Sensitivity		
	<0.625 eV	0.625 eV - 100 keV	>100 keV
<b>EC (Element Conf.) 1</b>	8.15E-03	1.81E-02	1.05E-01
<b>EC 2</b>	-2.19E-03	2.28E-03	9.43E-02
<b>EC 3</b>	9.81E-03	7.59E-03	3.25E-02
<b>EC 4</b>	3.51E-03	3.98E-03	4.53E-02
<b>EC 5</b>	-2.28E-02	2.66E-02	1.70E-01
<b>EC 6</b>	2.13E-02	4.46E-02	3.07E-01
<b>EC 7</b>	-1.66E-02	2.44E-02	1.35E-01
<b>EC 8</b>	-1.25E-02	4.57E-02	2.81E-01
<b>EC 9</b>	-6.79E-03	1.61E-02	1.54E-01
<b>EC 10</b>	-3.91E-03	4.17E-02	2.14E-01
<b>EC 11</b>	8.72E-04	1.32E-02	9.35E-02
<b>EC 12</b>	1.28E-02	3.04E-02	1.97E-01
<b>BaselineP</b>	-2.02E-02	3.95E-02	8.39E-02
<b>AlBeMet</b>	1.43E-02	2.40E-02	6.92E-02
<b>Offset</b>	2.06E-02	3.89E-02	7.30E-02
<b>Poly-Al-X</b>	1.02E-02	5.11E-03	7.36E-02
<b>HCI-003-002</b>	-1.89E-03	3.02E-02	2.29E-01
<b>HCI-003-005</b>	6.60E-04	3.30E-02	2.38E-01
<b>HMI-009-001</b>	1.74E-02	3.38E-01	6.21E-01
<b>HMT-027-001</b>	1.35E-01	5.96E-01	6.56E-01
<b>HMT-027-005</b>	3.26E-01	6.68E-01	6.19E-01


# Sensitivity Analysis – Beryllium Reactions




# Sensitivity Analysis – Beryllium Reactions




# Sensitivity Analysis – Beryllium Reactions



# Sensitivity Analysis - BeO Thermal Scattering (be/o + o/be)



# Sensitivity Analysis – $^{235}\text{U}$ Fission





# Ability/Benefits to Perform work

- Engage New Management for Support
  - BeO material is available
  - Operations staff knowledgeable/available
  - Ongoing fuel health campaign
- Unique fuel offers NCS useful data
  - Beryllium
  - Beryllium-oxide
  - $^{235}\text{U}$  enrichment in 7%-35% range
- Supports Nuclear Deterrence (ND) mission
- Documented Safety Analysis (DSA) Update is Straightforward
  - 7uPCX is driver fuel in designs and  $\text{UO}_2\text{-BeO}$  is considered experimental material
  - DSA enrichment limit is based on a  $\text{UO}_2$  fuel limit that is not challenged by  $\text{UO}_2\text{-BeO}$  fuel

# Conclusions

- ACRR fuel element experimental design for continued work
  - 7 ACRR elements
  - 7uPCX driver rods
- Beneficial data for
  - NCS community
  - ND community
- Support to perform work
  - Management
  - Operations
- Potential for multiple experiments



# Acknowledgements

This work was supported/funded through the DOE-NCSP and NNSA

Thanks to the many contributors of this study



**NUCLEAR CRITICALITY SAFETY PROGRAM**  
U.S. DEPARTMENT OF ENERGY

—  
Thank you.

Sandia  
National  
Laboratories

Managed for DOE by  
National Technology and  
Engineering Solutions of Sandia  
A Honeywell Company



United States  
Department of Energy



National Nuclear  
Security Administration



Questions?

# Elements Models -Critical Configuration Analysis

Changes to Critical Configuration	Replace BeO fueled region with void	Replace BeO fuel elements with void	Replace BeO fuel elements with aluminum	Replace BeO fuel elements with water	Replace BeO fuel elements with 7uPCX rods
Configuration 1 Reactivity Worth	-13.5181 ± -0.0948	-10.3075 ± -0.0979	-16.1149 ± -0.1017	-16.2319 ± -0.0977	1.2834 ± 0.1011
Configuration 2 Reactivity Worth	-24.2625 ± -0.0824	-20.7613 ± -0.0839	-26.561 ± -0.0900	-26.542 ± -0.0852	2.9149 ± 0.0871
Configuration 3 Reactivity Worth	-4.3836 ± -0.0945	-3.2337 ± -0.0985	-4.0093 ± -0.1027	-4.1024 ± -0.0992	0.7736 ± 0.0971
Configuration 4 Reactivity Worth	-8.8515 ± -0.0823	-6.9437 ± -0.0864	-9.7038 ± -0.0844	-9.6097 ± -0.0858	0.7643 ± 0.0849
Configuration 5 Reactivity Worth	-14.7035 ± -0.0964	-10.9869 ± -0.1001	-17.1763 ± -0.0972	-3.0607 ± -0.0984	1.5738 ± 0.0977
Configuration 6 Reactivity Worth	-25.0205 ± -0.0994	-20.6085 ± -0.0963	-27.411 ± -0.0941	1.0378 ± 0.0977	1.6266 ± 0.1054
Configuration 7 Reactivity Worth	-4.6148 ± -0.0893	-3.4198 ± -0.0892	-4.0263 ± -0.0935	-2.9815 ± -0.0956	0.8637 ± 0.0941
Configuration 8 Reactivity Worth	-8.7745 ± -0.0922	-6.7124 ± -0.0885	-9.4516 ± -0.0865	2.0391 ± 0.0870	0.4550 ± 0.0891
Configuration 9 Reactivity Worth	-14.7300 ± -0.0891	-11.1604 ± -0.0902	-13.0278 ± -0.0910	-3.3745 ± -0.0941	1.7113 ± 0.0978
Configuration 10 Reactivity Worth	-25.0673 ± -0.0991	-20.7851 ± -0.0992	-23.6253 ± -0.0952	1.5523 ± 0.0980	1.2238 ± 0.1000
Configuration 11 Reactivity Worth	-4.6198 ± -0.0984	-3.4316 ± -0.0928	-3.6237 ± -0.0915	-3.4636 ± -0.1005	0.7931 ± 0.0948
Configuration 12 Reactivity Worth	-8.7429 ± -0.0950	-6.7585 ± -0.0907	-7.8443 ± -0.0921	2.5517 ± 0.0899	0.1861 ± 0.0948